RX9030

TRACTOR



KIOTI

run ahead of the pack

SPECIFICATIONS

TECHNICAL DATA		RX9030PC
ENGINE		
Manufacturer		Daedong
Model		4FTA-TP2-A
Engine gross power	HP (max)	90
Rated revolution	rpm	2600
Туре		4 cylinder, in-line vertical water-cooled, commonrail diese
No. of cylinders		4
Total displacement	cc (cu in.)	2.435 (148.6)
Turbocharge		Turbo charged
Combustion system		Direct injection
ELECTRICITY		
Battery		12V-100AH(20h)
Horn		standard
7 pin socket		standard
Power socket		standard
DRIVE TRAIN		
Rated PTO power/rpm	HP (kw) /rpm	69.5
Maximum PTO power	HP (kw)	72.1
Transmission	, <i>,</i>	Power shuttle
Main gear shift x range gear shift		4 x 6
No. of speeds		24 x 24
Shuttle type		Power shuttle
Steering		Hydrostatic power steering
Rated PTO rpm	rpm	540 / 540E
·	rpm	574 / 785
PTO rpm @ Engine rated rpm	rpm	Wet multi disc
Main brake type		
Parking brake type		Wet multi disc
Main clutch type		Hydro multi wet disc clutch
Front wheel drive system		Hydro multi wet disc clutch
TRAVELLING SPEEDS		
Forward		0.17-37.66 (0.1-23.40)
Reverse		0.17-37.03 (0.1-23.01)
HYDRAULIC		
3-Point lift control type		Position, Draft, Mixed Control
Implement pump	lpm (cc/rev)	41.6 (16)
Power steering pump	lpm (cc/rev)	31.2 (12)
Total hydraulic flow	lpm (cc/rev)	72.8 (28)
3-point hitch type		Category II
Rear remote hydraulic valve	No of valves	2
	Port	1/2"
Joystick valve		standard
Auto PTO		standard
@lift point	kg.f (lbs)	2935 (6470)
Draft control		standard
Max. Trailer loading weight	kg.f (lbs)	6500 (14330)
DIMENSIONS		
Overall length (w/o front weight and w/o 3pt hitch)	mm	3730
Overall length (w/o front weight and with 3pt hitch)	mm	3915
Overall length (with weight support and with 3pt hitch)	mm	4090
Overall length (with front weight support and with 3pt hitch)	mm	4395
Overwall width (minimum tread)	mm	1960
Tread width - front	mm	1485
Tread width - rear	mm	1515
Overall height (Cab)	mm	2655
Wheel base	mm	2310
	mm	440
Ground (crop) clearance		
Ground (crop) clearance Turning radius (w/o brake)	mm	4140
Turning radius (w/o brake) Turning radius (with brake)	mm mm	4140 3590
Turning radius (w/o brake)		

*Note: The specifications are subject to change for the purpose of improvement without any notice.

STANDARD EQUIPMENT

- Air conditioner
- Heater
- Radio cassette player/bluetooth
- Sunvisor
- PTO cover
- Cup holder
- Rear view mirror
- Parking brake

